

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/014175 A1

(51) International Patent Classification⁷: **B05B 1/08, 1/14**

(21) International Application Number:
PCT/EP2004/007715

(22) International Filing Date: 13 July 2004 (13.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
103 32 434.8 16 July 2003 (16.07.2003) DE
103 32 426.7 16 July 2003 (16.07.2003) DE

(71) Applicant (for all designated States except US):
BOEHRINGER INGELHEIM MICROPARTS GMBH
[DE/DE]; Hauert 7, 44227 Dortmund (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SPITZ, Michael**

[DI/DE]; Gerrit-Engelke-Weg 14, 58675 Hermer (DI).
REINECKE, Holger [DI/DE]; Seepenweg 3, 44229
Dortmund (DI).


(74) Agent: **GESTHUYSEN, VON ROHR & EGGERT**;
Huyssenallee 100, 45128 Essen (DI).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: A PROCESS FOR PRODUCING MICROFLUIDIC ARRANGEMENTS FROM A PLATE-SHAPED COMPOSITE
STRUCTURE



(57) Abstract: This invention relates to a process for
producing a multiplicity of micro fluidic arrangements
(1) from a plate-shaped composite structure, wherein each
arrangement comprises a groove structure (4) which forms
flow channels and the dimensions of which are in the
micrometre range. The lines (6) for the optional subsequent
mechanical separation of bridging groove structures (4) are
joined to each other and are partly or completely filled with
a filling medium (7) before mechanical machining. The
medium (7) is selected so that it is not removed from the
groove structures (1) either by the mechanical machining
or by aids used during mechanical machining. Afterwards,
however, the filling medium (7) is removed from the groove
structures (6) by suitable measures. The groove structures
(4) are thereby prevented from becoming blocked due to
mechanical contaminants. An atomiser which is provided
with the nozzle arrangement is also proposed.

WO 2005/014175 A1

- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

— with international search report